

# Two Wheeler Batteries

SOLANCE®



## TECHNICAL FEATURES OF SOLANCE TWO WHEELER BATTERIES



### Inbuilt Terminal

Prevent acid seepage,  
reduce corrosion,  
extend battery life

### Heat Sealed Case to Cover

Bonded unit provide greater  
strength, protect against  
seepage and corrosion

### Polypropylene Cover and Container

Provide grater resistance  
to gas and oil, with  
stand higher impact in  
extreme condition

### AGM Separator

Make the battery  
spill-proof and  
eliminate water loss

### Safety Valve

Regulate inside gas pressure

### Through Partition Construction

Provide shorter current  
path with less resistance  
than over the partition

### Special Active Material











Compounded to withstand  
vibration prolong battery life  
and dependability

### Special Radial Grid Design









Withstand severe vibration,  
ensure maximum conductivity



### Motorcycle Batteries - Platinum Series

Battery Type	Rating Capacity @C20	Overall Battery Dimensions (±2.0 mm)			Nominal Filled Wt. (Kg) ±3%	Battery Layout	Warranty
		L	W	H			
SLX 2.5L	2.5Ah	81.0	71.0	104.0	1.12		24 FOC + 24 Pro-rata
SLZ 4L	4.0Ah	113.0	70.0	86.0	1.60		24 FOC + 24 Pro-rata
SLX 5L	5.0Ah	121.0	60.0	130.0	2.20		24 FOC + 24 Pro-rata
SLX 7R	7.0Ah	151.0	60.0	130.0	2.70		24 FOC + 24 Pro-rata
SLX 9R	9.0Ah	139.0	77.0	138.0	3.40		24 FOC + 24 Pro-rata
SLZ5L	5.0Ah	113.0	70.0	104.0	2.00		24 FOC + 24 Pro-rata
SLZ7L	7.0Ah	113.0	70.0	130.0	2.60		24 FOC + 24 Pro-rata
SLZ9R	9.0Ah	150.0	87.0	108.0	3.20		24 FOC + 24 Pro-rata
SLZ14R	14.0 Ah	150.0	87.0	146.0	4.80		24 FOC + 24 Pro-rata
SLZ14L	14.0 Ah	135.0	90.0	163.0	5.25		24 FOC + 24 Pro-rata

### Motorcycle Batteries - GOLD Series

Battery Type	Rating Capacity @C20	Overall Battery Dimensions (±2.0 mm)			Nominal Filled Wt. (Kg) ±3%	Battery Layout	Warranty
		L	W	H			
CLX 2.5L	2.5Ah	81.0	71.0	104.0	1.00		12 FOC + 12 Pro-rata
CLZ 4L	4.0Ah	113.0	70.0	86.0	1.40		12 FOC + 12 Pro-rata
CLX 5L	5.0Ah	121.0	60.0	130.0	1.80		12 FOC + 12 Pro-rata
CLX 7R	7.0Ah	151.0	60.0	130.0	2.30		12 FOC + 12 Pro-rata
CLX 9R	9.0Ah	139.0	77.0	138.0	3.00		12 FOC + 12 Pro-rata
CLZ5L	5.0Ah	113.0	70.0	104.0	1.80		12 FOC + 12 Pro-rata
CLZ7L	7.0Ah	113.0	70.0	130.0	2.40		12 FOC + 12 Pro-rata
CLZ9R	9.0Ah	150.0	87.0	108.0	2.90		12 FOC + 12 Pro-rata

Note : Specification are under continuous improvement. Subject to change without notice. \*New battery at pro rata warranty discounts on prevailing max. retail price.

## SOLANCE INDUSTRIES

📍 Plot No. 228, Vireshwar Industrial Estate, Nr. SKF Bearing, Bavla-Bagodara N.H.8A,  
Vill : Kerala, Tal.: Bavla, Ahmedabad, Gujarat - 382220, India.

☎ +91-722-600-4444 📧 info@solance.in

AUTOMOTIVE • TWO WHEELER • INVERTER • UPS • E-RICKSHAW • E-BIKE BATTERIES